




Rapid 80 plastic device installation trunking systems

	Device installation trunking, 1-compartment, trunking width 110 mm	290
	Device installation trunking, 1-compartment, trunking width 130 mm	294
	Device installation trunking, 1-compartment, trunking width 170 mm	298

Device installation trunking, type GK70110




Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-70110RW	Pure white	2000	8	132,000	6274 30 0
GK-70110CW	Cream	2000	8	132,000	6274 30 1
GK-70110LGR	Light grey	2000	8	132,000	6274 30 2
GK-70110GR	Stone grey	2000	8	132,000	6274 30 6

PVC Polyvinylchloride /m

GK device installation trunking, made of lead-free PVC, suitable for installing directly on the wall or on wall panels. Fastening takes place using the perforation in the trunking. The GK device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD... The system opening is 76.5 mm. On each trunking length a coupling pair is pre-assembled on one side.

Coupling




Type	Col-our	Pack. PU	Weight kg/100 PUs	Item No.
GK-KUP	Light grey	1	2,140	6274 65 0

ABS/ASA Acrylonitrile butadiene styrene /VPE

Coupling as trunking connector for tight connection of the trunking sections. A coupling pair is included and pre-mounted for each stock length.

Accessory mounting box, single




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD6	Iron grey	5	5,600	6288 61 0

PA Polyamide /pc.

Front locking accessory mounting box for switch systems, with folding, and also removable, base for time saving cable connection, with feed openings for cable diameters of up to 14 mm.

Accessory mounting box, double




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD7	Iron grey	2	11,000	6288 61 1

PA Polyamide /pc.

Front locking accessory mounting box for standard switch ranges for the installation of two individual installation devices or a multiple power socket.

Strain relief



Type	Pack. pcs	Weight kg/100 pcs.	Item No.
7ZE	50	0,700	6288 79 0

PA Polyamide /pc.

Strain relief with locking clips, suitable for the accessory mounting boxes 7GD... and 71GD... .

Trunking cover, smooth

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTGRW	Pure white	2000	16	27,500	6278 68 0
GK-OTGCW	Cream	2000	16	27,500	6278 68 1
GK-OTGLGR	Light grey	2000	16	27,500	6278 68 2
GK-OTGGR	Stone grey	2000	16	27,500	6278 68 6

PVC Polyvinylchloride

/m

Smooth trunking cover, for closing device installation trunking with 76.5 mm system opening.




Trunking cover, fluted

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTKRW	Pure white	2000	16	27,000	6278 78 0
GK-OTKCW	Cream	2000	16	27,000	6278 78 1
GK-OTKLGR	Light grey	2000	16	27,000	6278 78 2

PVC Polyvinylchloride

/m

Fluted trunking cover, for closing device installation trunking with 76.5 mm system opening.




External corner cover, variable

Type	Colour	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-AH70110RW	Pure white	130.5	1	15,000	6274 21 0
GK-AH70110CW	Cream	130.5	1	15,000	6274 21 1
GK-AH70110LGR	Light grey	130.5	1	15,000	6274 21 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

External corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH, GS and GA systems. The fittings can be variably adjusted between 80° and 100° and can be used in symmetrical and asymmetrical trunking.




External corner

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-A70110RW	Pure white	1	116,000	6274 31 0
GK-A70110CW	Cream	1	116,000	6274 31 1
GK-A70110LGR	Light grey	1	116,000	6274 31 2
GK-A70110GR	Stone grey	1	116,000	6274 31 6

PVC Polyvinylchloride

/pc.

External corner for changing the direction of the GK device installation trunking.




External corner cover, smooth

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGARW	Pure white	2	9,500	6274 79 0
GK-OTGACW	Cream	2	9,500	6274 79 1
GK-OTGALGR	Light grey	2	9,500	6274 79 2
GK-OTGAGR	Stone grey	2	9,500	6274 79 6


PVC Polyvinylchloride

/pc.

PVC external corner cover, smooth surface.



Flat angle cover




Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-FH70110RW	Pure white	152.5	1	15,100	6274 22 0
GK-FH70110CW	Cream	152.5	1	15,100	6274 22 1
GK-FH70110LGR	Light grey	152.5	1	15,100	6274 22 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.

Flat angle




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-F70110RW	Pure white	1	78,000	6274 32 0
GK-F70110CW	Cream	1	78,000	6274 32 1
GK-F70110LGR	Light grey	1	78,000	6274 32 2
GK-F70110GR	Stone grey	1	78,000	6274 32 6

PVC Polyvinylchloride

/pc.

Flat angle for changing the direction of the GK device installation trunking.

Flat angle cover, smooth




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGFRW	Pure white	1	17,000	6274 49 0
GK-OTGFCW	Cream	1	17,000	6274 49 1
GK-OTGFLGR	Light grey	1	17,000	6274 49 2
GK-OTGFGR	Stone grey	1	17,000	6274 49 6

PVC Polyvinylchloride

/pc.

Flat angle cover, smooth surface.

Internal corner cover, variable




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-IH70110RW	Pure white	1	14,200	6274 24 0
GK-IH70110CW	Cream	1	14,200	6274 24 1
GK-IH70110LGR	Light grey	1	14,200	6274 28 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Internal corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH GS and GA systems. The fittings can be variably adjusted between 85° and 95° and can be used in symmetrical and asymmetrical trunking.

Internal corner



Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-I70110RW	Pure white	1	100,000	6274 34 0
GK-I70110CW	Cream	1	100,000	6274 34 1
GK-I70110LGR	Light grey	1	100,000	6274 34 2
GK-I70110GR	Stone grey	1	100,000	6274 34 6

PVC Polyvinylchloride

/pc.

Internal corner for changing the direction of the GK device installation trunking.


T piece

Type	Col-our		Pack. Weight		Item No.
			pcs	kg/100 pcs.	
GK-T70110RW	Pure white		1	100,000	6274 36 0
GK-T70110CW	Cream		1	100,000	6274 36 1
GK-T70110LGR	Light grey		1	100,000	6274 36 2
GK-T70110GR	Stone grey		1	100,000	6274 36 6

PVC Polyvinylchloride

/pc.

T piece for changing the direction of the GK device installation trunking.




End piece

Type	Col-our		Pack. Weight		Item No.
			pcs	kg/100 pcs.	
GK-E70110RW	Pure white		1	4,900	6274 37 0
GK-E70110CW	Cream		1	4,900	6274 37 1
GK-E70110LGR	Light grey		1	4,900	6274 37 2
GK-E70110GR	Stone grey		1	4,900	6274 37 6

PVC Polyvinylchloride

/pc.

End piece for closing the GK device installation trunking.




Partition

Type	Col-our		Pack. Weight		Item No.
			m	kg/100 m	
GK-TW70	—		40	17,400	6274 90 0

PVC Polyvinylchloride

/m

Partition for mounting in Rapid 80 GK (GA) device installation trunking or ISS service poles for installing cables of different voltage levels.




Trunking clamp

Type		Pack. Weight		Item No.
		pcs	kg/100 pcs.	
KL80A		20	0,680	6288 64 0


PA Polyamide

/pc.

Trunking clamp for holding cables securely and for fastening the partition in Rapid 80 GK, GS and GA device installation trunking systems as well as in ISS service poles with a 76.5 system opening.



Device installation trunking, type GK70130




Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-70130RW	Pure white	2000	8	152,000	6274 50 0
GK-70130CW	Cream	2000	8	152,000	6274 50 1
GK-70130LGR	Light grey	2000	8	152,000	6274 50 2
GK-70130GR	Stone grey	2000	8	152,000	6274 50 6

PVC Polyvinylchloride

/m

GK device installation trunking, made of lead-free PVC, suitable for installing directly on the wall or on wall panels. Fastening takes place using the perforation in the trunking. The GK device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD... The system opening is 76.5 mm. On each trunking length a coupling pair is pre-assembled on one side.

Coupling





Type	Col-our	Pack. PU	Weight kg/100 PUs	Item No.
GK-KUP	Light grey	1	2,140	6274 65 0

ABS/ASA Acrylonitrile butadiene styrene

/PPE

Coupling as trunking connector for tight connection of the trunking sections. A coupling pair is included and pre-mounted for each stock length.

Accessory mounting box, single





Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD6	Iron grey	5	5,600	6288 61 0

PA Polyamide

/pc.

Front locking accessory mounting box for switch systems, with folding, and also removable, base for time saving cable connection, with feed openings for cable diameters of up to 14 mm.

Accessory mounting box, double





Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD7	Iron grey	2	11,000	6288 61 1

PA Polyamide

/pc.

Front locking accessory mounting box for standard switch ranges for the installation of two individual installation devices or a multiple power socket.

Strain relief



Type	Pack. pcs	Weight kg/100 pcs.	Item No.
7ZE	50	0,700	6288 79 0

PA Polyamide

/pc.

Strain relief with locking clips, suitable for the accessory mounting boxes 7GD... and 71GD... .


Trunking cover, smooth

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTGRW	Pure white	2000	16	27,500	6278 68 0
GK-OTGCW	Cream	2000	16	27,500	6278 68 1
GK-OTGLGR	Light grey	2000	16	27,500	6278 68 2
GK-OTGGR	Stone grey	2000	16	27,500	6278 68 6

PVC Polyvinylchloride

/m

Smooth trunking cover, for closing device installation trunking with 76.5 mm system opening.




Trunking cover, fluted

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTKRW	Pure white	2000	16	27,000	6278 78 0
GK-OTKCW	Cream	2000	16	27,000	6278 78 1
GK-OTKLGR	Light grey	2000	16	27,000	6278 78 2

PVC Polyvinylchloride

/m

Fluted trunking cover, for closing device installation trunking with 76.5 mm system opening.




External corner cover, variable

Type	Colour	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-AH70130RW	Pure white	130.5	1	16,100	6274 41 0
GK-AH70130CW	Cream	130.5	1	16,100	6274 41 1
GK-AH70130LGR	Light grey	130.5	1	16,100	6274 41 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

External corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH, GS and GA systems. The fittings can be variably adjusted between 80° and 100° and can be used in symmetrical and asymmetrical trunking.




External corner

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-A70130RW	Pure white	1	127,000	6274 51 0
GK-A70130CW	Cream	1	127,000	6274 51 1
GK-A70130LGR	Light grey	1	127,000	6274 51 2
GK-A70130GR	Stone grey	1	127,000	6274 51 6

PVC Polyvinylchloride

/pc.

External corner for changing the direction of the GK device installation trunking.




External corner cover, smooth

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGARW	Pure white	2	9,500	6274 79 0
GK-OTGACW	Cream	2	9,500	6274 79 1
GK-OTGALGR	Light grey	2	9,500	6274 79 2
GK-OTGAGR	Stone grey	2	9,500	6274 79 6


PVC Polyvinylchloride

/pc.

PVC external corner cover, smooth surface.



Flat angle cover




Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-FH70130RW	Pure white	172.5	1	17,100	6274 42 0
GK-FH70130CW	Cream	172.5	1	17,100	6274 42 1
GK-FH70130LGR	Light grey	172.5	1	17,100	6274 42 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.

Flat angle




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-F70130RW	Pure white	1	83,000	6274 52 0
GK-F70130CW	Cream	1	83,000	6274 52 1
GK-F70130LGR	Light grey	1	83,000	6274 52 2
GK-F70130GR	Stone grey	1	83,000	6274 52 6

PVC Polyvinylchloride

/pc.

Flat angle for changing the direction of the GK device installation trunking.

Flat angle cover, smooth




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGFRW	Pure white	1	17,000	6274 49 0
GK-OTGFCW	Cream	1	17,000	6274 49 1
GK-OTGFLGR	Light grey	1	17,000	6274 49 2
GK-OTGFGR	Stone grey	1	17,000	6274 49 6

PVC Polyvinylchloride

/pc.

Flat angle cover, smooth surface.

Internal corner cover, variable




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-IH70130RW	Pure white	1	14,900	6274 44 0
GK-IH70130CW	Cream	1	14,900	6274 44 1
GK-IH70130LGR	Light grey	1	14,900	6274 44 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Internal corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH GS and GA systems. The fittings can be variably adjusted between 85° and 95° and can be used in symmetrical and asymmetrical trunking.

Internal corner



Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-I70130RW	Pure white	1	110,000	6274 54 0
GK-I70130CW	Cream	1	110,000	6274 54 1
GK-I70130LGR	Light grey	1	110,000	6274 54 2
GK-I70130GR	Stone grey	1	110,000	6274 54 6

PVC Polyvinylchloride

/pc.

Internal corner for changing the direction of the GK device installation trunking.


T piece

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-T70130RW	Pure white	1	108,000	6274 56 0
GK-T70130CW	Cream	1	108,000	6274 56 1
GK-T70130LGR	Light grey	1	108,000	6274 56 2
GK-T70130GR	Stone grey	1	108,000	6274 56 6

PVC Polyvinylchloride

/pc.

T piece for changing the direction of the GK device installation trunking.




End piece

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-E70130RW	Pure white	1	5,400	6274 57 0
GK-E70130CW	Cream	1	5,400	6274 57 1
GK-E70130LGR	Light grey	1	5,400	6274 57 2
GK-E70130GR	Stone grey	1	5,400	6274 57 6

PVC Polyvinylchloride

/pc.

End piece for closing the GK device installation trunking.




Partition

Type	Col-our	Pack. m	Weight kg/100 m	Item No.
GK-TW70	—	40	17,400	6274 90 0

PVC Polyvinylchloride

/m

Partition for mounting in Rapid 80 GK (GA) device installation trunking or ISS service poles for installing cables of different voltage levels.




Trunking clamp

Type	Pack. pcs	Weight kg/100 pcs.	Item No.
KL80A	20	0,680	6288 64 0


PA Polyamide

/pc.

Trunking clamp for holding cables securely and for fastening the partition in Rapid 80 GK, GS and GA device installation trunking systems as well as in ISS service poles with a 76.5 system opening.



Device installation trunking, type GK70170




Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-70170RW	Pure white	2000	8	180,000	6274 70 0
GK-70170CW	Cream	2000	8	180,000	6274 70 1
GK-70170LGR	Light grey	2000	8	180,000	6274 70 2
GK-70170GR	Stone grey	2000	8	180,000	6274 70 6

PVC Polyvinylchloride

/m

GK device installation trunking, made of lead-free PVC, suitable for installing directly on the wall or on wall panels. Fastening takes place using the perforation in the trunking. The GK device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD... The system opening is 76.5 mm. On each trunking length a coupling pair is pre-assembled on one side.

Coupling





Type	Col-our	Pack. PU	Weight kg/100 PUs	Item No.
GK-KUP	Light grey	1	2,140	6274 65 0

ABS/ASA Acrylonitrile butadiene styrene

/VPE

Coupling as trunking connector for tight connection of the trunking sections. A coupling pair is included and pre-mounted for each stock length.

Accessory mounting box, single





Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD6	Iron grey	5	5,600	6288 61 0

PA Polyamide

/pc.

Front locking accessory mounting box for switch systems, with folding, and also removable, base for time saving cable connection, with feed openings for cable diameters of up to 14 mm.

Accessory mounting box, double





Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD7	Iron grey	2	11,000	6288 61 1

PA Polyamide

/pc.

Front locking accessory mounting box for standard switch ranges for the installation of two individual installation devices or a multiple power socket.

Strain relief



Type	Pack. pcs	Weight kg/100 pcs.	Item No.
7ZE	50	0,700	6288 79 0

PA Polyamide

/pc.

Strain relief with locking clips, suitable for the accessory mounting boxes 7GD... and 71GD... .

Trunking cover, smooth

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTGRW	Pure white	2000	16	27,500	6278 68 0
GK-OTGCW	Cream	2000	16	27,500	6278 68 1
GK-OTGLGR	Light grey	2000	16	27,500	6278 68 2
GK-OTGGR	Stone grey	2000	16	27,500	6278 68 6

PVC Polyvinylchloride

/m

Smooth trunking cover, for closing device installation trunking with 76.5 mm system opening.




Trunking cover, fluted

Type	Colour	Length mm	Pack. m	Weight kg/100 m	Item No.
GK-OTKRW	Pure white	2000	16	27,000	6278 78 0
GK-OTKCW	Cream	2000	16	27,000	6278 78 1
GK-OTKLGR	Light grey	2000	16	27,000	6278 78 2

PVC Polyvinylchloride

/m

Fluted trunking cover, for closing device installation trunking with 76.5 mm system opening.




External corner cover, variable

Type	Colour	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-AH70170RW	Pure white	130.5	1	18,500	6274 61 0
GK-AH70170CW	Cream	130.5	1	18,500	6274 61 1
GK-AH70170LGR	Light grey	130.5	1	18,500	6274 61 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

External corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH, GS and GA systems. The fittings can be variably adjusted between 80° and 100° and can be used in symmetrical and asymmetrical trunking.




External corner

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-A70170RW	Pure white	1	149,000	6274 71 0
GK-A70170CW	Cream	1	149,000	6274 71 1
GK-A70170LGR	Light grey	1	149,000	6274 71 2
GK-A70170GR	Stone grey	1	149,000	6274 71 6

PVC Polyvinylchloride

/pc.

External corner for changing the direction of the GK device installation trunking.




External corner cover, smooth

Type	Colour	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGARW	Pure white	2	9,500	6274 79 0
GK-OTGACW	Cream	2	9,500	6274 79 1
GK-OTGALGR	Light grey	2	9,500	6274 79 2
GK-OTGAGR	Stone grey	2	9,500	6274 79 6


PVC Polyvinylchloride

/pc.

PVC external corner cover, smooth surface.



Flat angle cover




Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-FH70170RW	Pure white	212.5	1	21,600	6274 62 0
GK-FH70170CW	Cream	212.5	1	21,600	6274 62 1
GK-FH70170LGR	Light grey	212.5	1	21,600	6274 62 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.

Flat angle




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-F70170RW	Pure white	1	91,000	6274 72 0
GK-F70170CW	Cream	1	91,000	6274 72 1
GK-F70170LGR	Light grey	1	91,000	6274 72 2
GK-F70170GR	Stone grey	1	91,000	6274 72 6

PVC Polyvinylchloride

/pc.

Flat angle for changing the direction of the GK device installation trunking.

Flat angle cover, smooth




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-OTGFRW	Pure white	1	17,000	6274 49 0
GK-OTGFCW	Cream	1	17,000	6274 49 1
GK-OTGFLGR	Light grey	1	17,000	6274 49 2
GK-OTGFGR	Stone grey	1	17,000	6274 49 6

PVC Polyvinylchloride

/pc.

Flat angle cover, smooth surface.

Internal corner cover, variable




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-IH70170RW	Pure white	1	16,300	6274 64 0
GK-IH70170CW	Cream	1	16,300	6274 64 1
GK-IH70170LGR	Light grey	1	16,300	6274 64 2

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene

/pc.

Internal corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH GS and GA systems. The fittings can be variably adjusted between 85° and 95° and can be used in symmetrical and asymmetrical trunking.

Internal corner



Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-I70170RW	Pure white	1	130,000	6274 74 0
GK-I70170CW	Cream	1	130,000	6274 74 1
GK-I70170LGR	Light grey	1	130,000	6274 74 2
GK-I70170GR	Stone grey	1	130,000	6274 74 6

PVC Polyvinylchloride

/pc.

Internal corner for changing the direction of the GK device installation trunking.


T piece

Type	Col-our		Pack. Weight		Item No.
			pcs	kg/100 pcs.	
GK-T70170RW	Pure white		1	120,000	6274 76 0
GK-T70170CW	Cream		1	120,000	6274 76 1
GK-T70170LGR	Light grey		1	120,000	6274 76 2
GK-T70170GR	Stone grey		1	120,000	6274 76 6

PVC Polyvinylchloride

/pc.

T piece for changing the direction of the GK device installation trunking.




End piece

Type	Col-our		Pack. Weight		Item No.
			pcs	kg/100 pcs.	
GK-E70170RW	Pure white		1	4,900	6274 77 0
GK-E70170CW	Cream		1	4,900	6274 77 1
GK-E70170LGR	Light grey		1	4,900	6274 77 2
GK-E70170GR	Stone grey		1	4,900	6274 77 6

PVC Polyvinylchloride

/pc.

End piece for closing the GK device installation trunking.




Partition

Type	Col-our		Pack. Weight		Item No.
			m	kg/100 m	
GK-TW70	—		40	17,400	6274 90 0

PVC Polyvinylchloride

/m

Partition for mounting in Rapid 80 GK (GA) device installation trunking or ISS service poles for installing cables of different voltage levels.



Trunking clamp

Type		Pack. Weight		Item No.
		pcs	kg/100 pcs.	
KL80A		20	0,680	6288 64 0

PA Polyamide

/pc.

Trunking clamp for holding cables securely and for fastening the partition in Rapid 80 GK, GS and GA device installation trunking systems as well as in ISS service poles with a 76.5 system opening.

