



Rapid 80 plastic device installation trunking systems, halogen-free




Device installation trunking, 1-compartment, trunking width 130 mm 304



Device installation trunking, 1-compartment, trunking width 170 mm 307

Device installation trunking, type GKH70130




Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-70130RW	Pure white	2000	8	121,000	6114 20 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m

GKH device installation trunking made of halogen-free PC/ABS, suitable for direct wall mounting or on wall brackets. Fastening takes place using the perforation in the trunking. The GKH device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD.... The system opening is 76.5 mm. On each trunking length, a coupling pair is pre-assembled on one side.

Coupling




Type	Col-our	Pack. PU	Weight kg/100 PUs	Item No.
GK-KUP	Light grey	1	2,140	6274 65 0

ABS/ASA Acrylonitrile butadiene styrene /VPE

Coupling as trunking connector for tight connection of the trunking sections. A coupling pair is included and pre-mounted for each stock length.

Accessory mounting box, single




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD6	Iron grey	5	5,600	6288 61 0

PA Polyamide /pc.

Front locking accessory mounting box for switch systems, with folding, and also removable, base for time saving cable connection, with feed openings for cable diameters of up to 14 mm.

Accessory mounting box, double




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD7	Iron grey	2	11,000	6288 61 1

PA Polyamide /pc.

Front locking accessory mounting box for standard switch ranges for the installation of two individual installation devices or a multiple power socket.

Strain relief



Type	Pack. pcs	Weight kg/100 pcs.	Item No.
7ZE	50	0,700	6288 79 0

PA Polyamide /pc.

Strain relief with locking clips, suitable for the accessory mounting boxes 7GD... and 71GD... .

Trunking cover, smooth



Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-OTGRW	Pure white	2000	1	22,000	6114 21 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m


Smooth trunking cover made of halogen-free PC/ABS, for closing device installation trunking with 80 mm system opening.

External corner cover, variable

Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-AH70130RW	Pure white	130.5	1	16,100	6274 41 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

External corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH, GS and GA systems. The fittings can be variably adjusted between 80° and 100° and can be used in symmetrical and asymmetrical trunking.




External corner

Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-A70130RW	Pure white		1	100,000	6114 22 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

External corner made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.




External corner cover, smooth

Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-OTGARW	Pure white		2	7,500	6114 23 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

PC/ABS external corner cover, smooth surface.




Flat angle cover

Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-FH70130RW	Pure white	172.5	1	17,100	6274 42 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.




Flat angle

Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-F70130RW	Pure white		1	66,000	6114 24 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

Flat angle made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.




Flat angle cover, smooth


Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-OTGFRW	Pure white		1	13,000	6114 25 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

Flat angle cover made of halogen-free PC/ABS.



Internal corner cover, variable




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-IH70130RW	Pure white	1	14,900	6274 44 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

Internal corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH GS and GA systems. The fittings can be variably adjusted between 85° and 95° and can be used in symmetrical and asymmetrical trunking.

Internal corner




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-I70130RW	Pure white	1	90,000	6114 26 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

Internal corner made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.

T piece




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-T70130RW	Pure white	1	82,000	6114 27 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

T piece made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.

End piece




Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-E70130RW	Pure white	1	4,600	6114 28 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.

End piece made of halogen-free PC/ABS for closing the GKH device installation trunking.

Partition




Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-TW70	Pure white	2000	40	14,000	6114 29 0

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m

Partition made of halogen-free PC/ABS for mounting in Rapid 80 GKH (GA) device installation trunking or ISS service poles for installing cables of different voltage levels.

Trunking clamp



Type	Pack. pcs	Weight kg/100 pcs.	Item No.
KL80A	20	0,680	6288 64 0


PA Polyamide /pc.

Trunking clamp for holding cables securely and for fastening the partition in Rapid 80 GK, GS and GA device installation trunking systems as well as in ISS service poles with a 76.5 system opening.

Device installation trunking, type GKH70170

Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-70170RW	Pure white	2000	8	151,000	6114 30 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m					


GKH device installation trunking made of halogen-free PC/ABS, suitable for direct wall mounting or on wall brackets. Fastening takes place using the perforation in the trunking. The GKH device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD.... The system opening is 76.5 mm. On each trunking length, a coupling pair is pre-assembled on one side.



Coupling

Type	Col-our	Pack. PU	Weight kg/100 PUs	Item No.
GK-KUP	Light grey	1	2,140	6274 65 0
ABS/ASA Acrylonitrile butadiene styrene /VPE				


Coupling as trunking connector for tight connection of the trunking sections. A coupling pair is included and pre-mounted for each stock length.



Accessory mounting box, single

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD6	Iron grey	5	5,600	6288 61 0
PA Polyamide /pc.				


Front locking accessory mounting box for switch systems, with folding, and also removable, base for time saving cable connection, with feed openings for cable diameters of up to 14 mm.



Accessory mounting box, double

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
71GD7	Iron grey	2	11,000	6288 61 1
PA Polyamide /pc.				


Front locking accessory mounting box for standard switch ranges for the installation of two individual installation devices or a multiple power socket.



Strain relief

Type	Pack. pcs	Weight kg/100 pcs.	Item No.
7ZE	50	0,700	6288 79 0
PA Polyamide /pc.			


Strain relief with locking clips, suitable for the accessory mounting boxes 7GD... and 71GD... .




Trunking cover, smooth

Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-OTGRW	Pure white	2000	1	22,000	6114 21 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m					

Smooth trunking cover made of halogen-free PC/ABS, for closing device installation trunking with 80 mm system opening.




External corner cover, variable



Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-AH70170RW	Pure white	130.5	1	18,500	6274 61 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

External corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH, GS and GA systems. The fittings can be variably adjusted between 80° and 100° and can be used in symmetrical and asymmetrical trunking.


External corner



Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-A70170RW	Pure white		1	119,000	6114 32 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

External corner made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.


External corner cover, smooth



Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-OTGARW	Pure white		2	7,500	6114 23 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

PC/ABS external corner cover, smooth surface.


Flat angle cover



Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-FH70170RW	Pure white	212.5	1	21,600	6274 62 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.


Flat angle



Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-F70170RW	Pure white		1	73,000	6114 34 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

Flat angle made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.

Flat angle cover, smooth




Type	Col-our	Length mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-OTGFRW	Pure white		1	13,000	6114 25 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene					/pc.

Flat angle cover made of halogen-free PC/ABS.

Internal corner cover, variable

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GK-IH70170RW	Pure white	1	16,300	6274 64 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.				


Internal corner cover made of halogen-free PC/ABS for changing the direction of Rapid 80 device installation trunking of the GK, GKH GS and GA systems. The fittings can be variably adjusted between 85° and 95° and can be used in symmetrical and asymmetrical trunking.



Internal corner

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-I70170RW	Pure white	1	100,000	6114 36 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.				


Internal corner made of halogen-free PC/ABS for changing the direction of the GK device installation trunking.



T piece

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-T70170RW	Pure white	1	96,000	6114 37 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.				


T piece made of halogen-free PC/ABS for changing the direction of the GKH device installation trunking.



End piece

Type	Col-our	Pack. pcs	Weight kg/100 pcs.	Item No.
GKH-E70170RW	Pure white	1	4,000	6114 38 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.				


End piece made of halogen-free PC/ABS for closing the GKH device installation trunking.



Partition

Type	Col-our	Length mm	Pack. m	Weight kg/100 m	Item No.
GKH-TW70	Pure white	2000	40	14,000	6114 29 0
PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /m					

Partition made of halogen-free PC/ABS for mounting in Rapid 80 GKH (GA) device installation trunking or ISS service poles for installing cables of different voltage levels.



Trunking clamp

Type	Pack. pcs	Weight kg/100 pcs.	Item No.
KL80A	20	0,680	6288 64 0
PA Polyamide /pc.			

Trunking clamp for holding cables securely and for fastening the partition in Rapid 80 GK, GS and GA device installation trunking systems as well as in ISS service poles with a 76.5 system opening.

