

PYROBAG® cushion insulation

PYROBAG® cushion insulation



Cushion


218



Identification plate

218

PYROBAG® fire protection cushion




Type	Dim. B mm	Dimen- sion D mm	Pack. pcs	Weight kg/100 pcs.	Item No.
KBK-1	120	10	20	18,000	7202 70 9
KBK-2	170	23	20	33,000	7202 72 5
KBK-3	170	40	10	63,000	7202 74 1

Glass mesh with special fire protection filling /pc.

Cable fire protection cushions made of dense, closely-knit and mechanically solid glass mesh with a special filling. Free from mineral fibres, weatherproof and water-resistant. Can be stored for an unlimited period of time in dry, frost-free rooms.

Calcium silicate plate




Type	Dim. L mm	Dim. B mm	Dimen- sion D mm	Pack. pcs	Weight kg/100 pcs.	Item No.
KSI-P1	500	150	20	1	42,000	7202 28 3
KSI-P2	500	250	30	1	111,000	7202 90 4
KSI-P3	1000	250	30	1	222,000	7202 91 2

Calcium silicate /pc.

Calcium silicate plate, as support plate, for the construction of frames in the penetration and to double thin wall thicknesses. Materials class EN 13501 - A1 non-combustible.

Steel wire grid




Type	Dim. L mm	Dim. B mm	Pack. pcs	Weight kg/100 pcs.	Item No.
SDG-1	600	500	1	135,000	7202 96 3
SDG-2	1000	600	1	270,000	7202 97 1

Steel /pc.

FT Hot-dip galvanised

Steel wire grid as support and protection grid, wire diameter 4 mm.

Bolt tie for steel wire grid




Type	Dimension mm	Anchor length mm	Bore hole Ø mm	Head Ø mm	Screw system	Pack. pcs	Weight kg/100 pcs.	Item No.
MMS-MS7,5x50	7.5 x 50	50	6	17	Torx	100	1,522	3498 26 0

Steel /100 pc.

G Electrogalvanised

Fire protection bolt tie with large pan head for direct mounting without additional anchors. Drive T30, drill hole 6 mm. Fire protection tested according to DIN 4102 for concrete and masonry.

Identification plate



Type	Language	Pack. pcs	Weight kg/100 pcs.	Item No.
KS-S DE	German	1	2,400	7205 42 5
KS-S SE	Swedish	1	2,400	7205 42 6
KS-S ES	Spanish	1	2,400	7205 42 7
KS-S EN	English	1	2,400	7205 42 9
KS-S HR	Croatian	1	2,400	7205 43 8

PVC Polyvinylchloride /pc.

Universal identification plate to be written on with waterproof and light-resistant felt-tip pen for all types of OBO insulation. For approved identification, including two push-fit anchors.

