





Contents: Pipe shell PYROCOMB® Tubes

	Pipe shell	234
	Half shell	234
	Ablation coating	234
	Identification plate	235



PYROCOMB® Intube pipe shells



Type	Dimen- sion D mm	Dim. L mm	Dim. B mm	For opening Ø mm	Pack. pcs	Weight kg/100 pcs.	Item No.
CTS-150	116	150	120	125	1	35,200	7204 30 0
CTS-300	116	300	120	125	1	70,000	7204 30 4


PVC Polyvinylchloride /pc.

Internally coated pipe shells with click lock. The inner space can be fitted with cables and electrical installation pipes completely. Approved in Europe with ETA-13/0904. Fire resistance classes to EI120.

Closing with 2 foam plugs included in the delivery. The surface seal is created with the ASX coating.

In some applications, the use of metallic tightening strips is prescribed to secure the pipe shells in light-duty partitions. Details can be found in the mounting instructions/approval.

PYROCOMB® Intube half shell



Type	Diameter mm	Length mm	For opening Ø mm	Pack. pcs	Weight kg/100 pcs.	Item No.
CTS-HP200	116	200	125	1	20,000	7204 30 6

PVC Polyvinylchloride /pc.

Internally-coated half shell, the inner space of which can be fully assigned with cables and electrical installation pipes. Approved in Europe with ETA-13/0904. Fire resistance classes to EI120.

Closing with foam plug included in the delivery. The surface seal is done with ASX coating.

The system is particularly suitable for underfloor areas.

Details can be found in the mounting instructions/approval.

Ablation coating in a cartridge



Type	Contents ml	Pack. pcs	Weight kg/100 pcs.	Item No.
ASX-K	310	1	50,000	7202 31 0

Intumescent material /pc.

Combined, endothermic and weatherproof coating for internal and external areas. Universal protection coating for cable and cable support structures. Use as direct filler, as paint when stirred.

Material class DIN 4102 - B2, normally flammable.

In dry, frost-free rooms, the coating can be stored at temperatures from +5 °C to +25 °C for up to 18 months in closed, upright original containers.

Ablation coating in a bucket



Type	Contents kg	Pack. pcs	Weight kg/100 pcs.	Item No.
ASX-E	5	1	500,000	7202 31 2

Intumescent material /pc.

Combined, endothermic and weatherproof coating for internal and external areas. Universal protection coating for cable and cable support structures. Use as direct filler, and as paint when stirred. Sufficient for an area of 4 m².

Material class DIN 4102 - B2, normally flammable.

In dry, frost-free rooms, the coating can be stored at temperatures from +5 °C to +25 °C for up to 18 months in closed, upright original containers.

Mortar in bucket for group arrangements



Type	Contents kg	Pack. pcs	Weight kg/100 pcs.	Item No.
MSX-E1	10	1	1.000,000	7206 05 8

Special mortar /pc.

Mortar to create cable and combination insulation in solid walls and ceilings. Suitable for pumping, pressing and for manual installation. Adding approx. 3 litres of water to 10 kg of dry mortar produces about 10 litres of workable compound.

In dry, frost-free rooms, the dry mortar can be stored for at least 12 months in closed original containers.

Mortar in paper sack for group arrangements

Type	Contents kg	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
MSX-S1	20	1	2.000,000	7206 10 4

Special mortar /pc.

Mortar to create cable and combination insulation in solid walls and ceilings. Suitable for pumping, pressing and for manual installation. Adding approx. 6 litres of water to 20 kg of dry mortar produces about 20 litres of workable compound.

In dry, frost-free rooms, the dry mortar can be stored for at least 12 months in closed original containers.



Metal strip clip for securing in lightweight partitions

Type	Length mm	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
MBS 045	450	50	0,602	7203 10 4

V2A Stainless steel, grade 304 /100 pc.

Metal strip clip in ladder form with single lock, 7 mm wide in various fixed lengths. For high-temperature and weatherproof fixing.



Identification plate

Type	Language	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
KS-S DE	German	1	2,400	7205 42 5
KS-S SE	Swedish	1	2,400	7205 42 6
KS-S ES	Spanish	1	2,400	7205 42 7
KS-S EN	English	1	2,400	7205 42 9
KS-S HR	Croatian	1	2,400	7205 43 8

PVC Polyvinylchloride /pc.

Universal identification plate to be written on with waterproof and light-resistant felt-tip pen for all types of OBO insulation. For approved identification, including two push-fit anchors.

