









PYROPLUG® foam series

PYROPLUG® foam series

	Foam block	222
	Plugs	222
	Box insulation	222
	Pipe shells	223
	Filler	223
	Identification plate	225


PYROPLUG® Block foam block



Type	Dimension mm	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
FBA-B200-14	200x144x60	4	44,800	7202 50 5

Permanently elastic, closed-pore foam /pc.
 Foam block for cable and combination insulation, can also be used as a filler block in the PYROSIT® NG fire protection foam system.
 The blocks must be protected against water in order to guarantee safe expansion in the case of fire.

PYROPLUG® Block vacuum block



Type	Dimension mm	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
FBA-BV200-14	200x144x25	1	40,000	7202 51 5

Permanently elastic, closed-pore foam /pc.
 Vacuum block for cable and combination insulation.
 After cutting into the foil the vacuum block expands to its original size. It can be used with or without foil.
 The blocks must be protected against water in order to guarantee safe expansion in the case of fire.


2-component fire protection foam PYROSIT® NG



Type	Contents ml	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
FBS-S	380	1	64,600	7203 80 0

/pc.
 PYROSIT® NG 2-component fire protection foam in a cartridge, including 2 mixing tubes.
 To create cable and combination insulation; always process with the cartridge pistols FBS-PH or FBS-PA.
 In dry, frost-free rooms, the cartridge can be stored closed and standing upright at temperatures from +5 °C to +30 °C for up to 12 months.


PYROPLUG® Peg plugs



Type	For opening			Dimen- sion D mm	Dim. d mm	Pack. Weight		Item No.
	Ø mm	mm	mm			pcs	kg/100 pcs.	
FBA-SN65	55	75	65	4	8,200	7202 55 3		
FBA-SN78	68	87	78	4	12,600	7202 55 7		
FBA-SN107	97	117	107	4	21,600	7202 56 1		
FBA-SN122	112	132	122	4	28,600	7202 56 5		
FBA-SN134	124	144	134	4	32,900	7202 56 9		
FBA-SN165	155	175	165	2	49,700	7202 57 3		
FBA-SN200	190	210	200	2	74,400	7202 57 7		
FBA-SN250	240	260	250	2	101,400	7202 58 1		

Permanently elastic, closed-pore foam /pc.
 Plug for cable insulation
 Protect the FBA plugs against water in order to guarantee safe foaming in case of fire.

PYROLPUG® Box box insulation



Type	Dimension mm	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
FBA-F	200 x 200 x 100	1	122,000	7202 66 0

Permanently elastic, closed-pore foam /pc.
 Box for cable insulation.
 Consisting of a two-part, hard frame and two soft internal pieces. Protect the frame and internal pieces against water in order to guarantee safe foaming in case of fire.

PYROPLUG® Shell drill crown insulation



Type	Dim.	Pack.	Weight		Item No.
	L mm		pcs	kg/100 pcs.	
FBA-D100	100	4	15,500		7202 62 4
FBA-D150	150	8	19,200		7202 62 8

Permanently elastic, closed-pore foam

/pc.

Pipe shell for cable insulation.

Consisting of a one-part, hard pipe sleeve and two soft plugs of 50 mm diameter. Protect the pipe sleeves and plugs against water in order to guarantee safe foaming in case of fire.



Empty mini pipe shell



Type	Dim.	Pack.	Weight		Item No.
	L mm		pcs	kg/100 pcs.	
FBA-DR100	100	6	6,500		7202 61 3
FBA-DR150	150	9	10,200		7202 61 7

Permanently elastic, closed-pore foam

/pc.

Empty pipe sleeve for use in FBA-SP small insulation in lightweight partitions.

Protect the pipe sleeves against water in order to guarantee safe foaming in case of fire.



PYROPLUG® Screed filler

Type	Contents	Pack.	Weight		Item No.
	ml		pcs	kg/100 pcs.	
FBA-SP	310	1	46,000		7202 32 2

Intumescent material

/pc.

Fire protection filler in a cartridge.

Usable as small insulation and as joint closing compound in all insulation of the PYROPLUG® series.

In dry, frost-free rooms, the fire protection filler can be stored for up to 12 months at a temperature of +5 °C to +30 °C.



Section insulation for metal pipes

Type	Length	Width	Thickness	Pack.	Weight		Item No.
	mm	mm	mm		pcs	kg/100 pcs.	
MIW-MA	8000	500	30	2	1.010,000		7202 30 8

Mineral fibres

/pc.

Mineral wool mats with aluminium lamination for section insulation on copper and steel pipes. Fastening with winding wire, securing of joints with aluminium adhesive tape.

Applicable in the systems:

PYROMIX® mortar insulation

PYROSIT® fire insulation foam

PYROPLATE® Fibre soft insulation

PYROPLUG® Block stones

Material class EN 13501 - A1 non-combustible; melting point ≥ 1,000 °C



Aluminium adhesive tape for section insulation

Type	Length	Pack.	Weight		Item No.
	mm		pcs	kg/100 pcs.	
MIW-AT	10000	1	136,900		7202 30 5

/pc.

Aluminium adhesive tape for applying the aluminium-laminated section insulation. The aluminium adhesive tape is self-adhesive and not classified as combustible according to DIN 4102-1.



Winding wire for section insulation



Type	Length mm	Pack. Weight		Item No.
		pcs	kg/100 pcs.	
MIW-TD	50000	1	10,000	7202 30 9
SI Steel				/pc.
VZ Galvanised				

The steel wire is used to fix the section insulation. It is non-combustible and guarantees optimum retention of the section insulation on non-combustible pipes and cables.


Cable coil



Type	Width mm	Length mm	Pack. Weight		Item No.
			pcs	kg/100 pcs.	
FBA-WI	150	5000	2	83,000	7202 51 0
					/pc.

Self-adhesive, intumescent cable protector, 5 mm thick, for the use with small cable diameters and pass-through cable support systems, applicable in PYROPLUG® systems and PYROSIT® NG.


Calcium silicate plate



Type	Dim. L mm	Dim. B mm	Dimen- sion D mm	Pack. Weight		Item No.
				pcs	kg/100 pcs.	
KSI-P1	500	150	20	1	42,000	7202 28 3
KSI-P2	500	250	30	1	111,000	7202 90 4
KSI-P3	1000	250	30	1	222,000	7202 91 2

Calcium silicate
Calcium silicate plate, as support plate, for the construction of frames in the penetration and to double thin wall thicknesses.
Materials class EN 13501 - A1 non-combustible.


Steel wire grid



Type	Dim. L mm	Dim. B mm	Pack. Weight		Item No.
			pcs	kg/100 pcs.	
SDG-1	600	500	1	135,000	7202 96 3
SDG-2	1000	600	1	270,000	7202 97 1

SI Steel
FI Hot-dip galvanised
Steel wire grid as support and protection grid, wire diameter 4 mm.

Bolt tie for steel wire grid



Type	Dimension mm	Anchor length mm	Bore hole Ø mm	Head Ø mm	Screw system	Pack. Weight		Item No.
						pcs	kg/100 pcs.	
MMS-MS7,5x50	7.5 x 50	50	6	17	Torx	100	1,522	3498 26 0
SI Steel								/100 pc.
G Electrogalvanised								


Fire protection bolt tie with large pan head for direct mounting without additional anchors. Drive T30, drill hole 6 mm. Fire protection tested according to DIN 4102 for concrete and masonry.

Identification plate

Type	Language	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
KS-S DE	German	1	2,400	7205 42 5
KS-S SE	Swedish	1	2,400	7205 42 6
KS-S ES	Spanish	1	2,400	7205 42 7
KS-S EN	English	1	2,400	7205 42 9
KS-S HR	Croatian	1	2,400	7205 43 8

PVC Polyvinylchloride

/pc.



Universal identification plate to be written on with waterproof and light-resistant felt-tip pen for all types of OBO insulation. For approved identification, including two push-fit anchors.

